SELLO
2 IN 1 WALL PRIMER

SELLO 2 in 1 Wall Primer is a single pack water based primer for interior / exterior walls

PRODUCT FEATURES

DRYING TIME

TACK FREE
20 - 30 minutes
HARD DRY
72 hours

AVAILABLE PACKS

1L, 4L, 10L, 20L

COVERAGE

Interior - 80-100sq.ft / 1 coat / litre
Exterior -50-60sq.ft / 1 coat / litre

* Coverage varies depends on the method of application and absorption of the substrate and its condition

MRF Vapocure Paints



PRODUCT BENEFITS

Advantages

- Value for money
- Good coverage
- Best in its class

Where to use

Designed for use on cement plastered exterior walls as primer for Campus, Visa and Visa Shine interior / exterior emulsion

HOW TO APPLY

SURFACE PREPARATION

- Ensure that the surface is clean and free from dampness , dirt and other contamination
- For areas severally affected by algae and fungi ,ensure that the surface is completely cleaned before initiating the painting process
- Sand the surface using Emery Paper No. 180 and clean thoroughly. Ensure that no loose particles are sticking to the wall
- Freshly plastered surfaces must be allowed to cure completely. The coating process can be started after a minimum period of 30 days

APPLICATION PROCESS

- Apply 1 - 2 coats of SELLO 2 in 1 Wall Primer with an interval of 3 - 4 hrs between subsequent coats
- Scuffing of the second coat of SELLO 2 in 1 Wall Primer with Emery No. 320
- Apply 2 coats of Campus / Campus Shine / Visa / Visa Shine shades as per recommendation

TECHNICAL INFO

Thinner Intake	- 60 – 70 %
Specific gravity	- 1.48 ± 0.03
Non Volatile Matter	- 55.00 ± 2
Typical thickness	- 40 – 45microns/coat
VOC	- < 50 g /l
Recommended Thinner	- Potable Water
Method of application	- Brush / Roller

ADDITIONAL INFORMATION

PRECAUTIONS

The substrate to be coated should be free from dampness as it directly relates to premature paint failure The product should be applied at temperatures falling between 20°C to 40°C for optimum performance. Humidity above 75 % is also not favourable The product should be stored in a dry, cool and well ventilated place.

PRODUCT DISCLAIMER

The information furnished above are true to the best of our knowledge. The properties specified were tested under controlled conditions. The results may vary depending on the test conditions, condition of the substrate and the test method employed. We are not liable for factors that are beyond our knowledge and control.

SHELF LIFE

3 Years from the month of manufacturing for an unopened original container.